



# Slicer Selection Guide

shop.dinecompany.com

Model No.	Slicing Volume ///////// (30 Minutes to All Day)	Precision Slicing Index	Manual (Slice to Order)	Automatic (Bulk Slicing)	Cheese Slicing	Drive Type	Construction	Motor	Blade (Diameter)	Max. Slice Thickness	Cutting Capacity		
											D (Diameter)	W (Width)	H (Height)
<b>Globe P-Series Heavy Duty Premium Slicers</b>													
3600P - 4600P	All Day 	●	✓		●	Gear	Stainless Steel	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	7.5" (19.50cm)	11.6" (29.46cm)	9" (22.86cm)
3850P (2 Speed)	All Day 	●	✓	✓	●	Gear	Stainless Steel	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	7.5" (19.50cm)	11.6" (29.46cm)	9" (22.86cm)
3975P - 4975P (9 Speed)	All Day 	●	✓	✓	●	Gear	Stainless Steel	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	7.5" (19.50cm)	11.6" (29.46cm)	9" (22.86cm)
<b>Globe G-Series Medium Duty Slicers</b>													
GC512	4 Hours 	◐	✓		◐	Gear	Aluminum/ Stainless Steel	1/3 HP	12" (30.48cm)	7/8" (2.22cm)	7.5" (19.50cm)	10" (25.40cm)	8.75" (22.23cm)
G14	3 Hours 	◐	✓		◐	Belt	Aluminum	1/2 HP	14" (35.56cm)	9/16" (1.43cm)	9.75" (24.8cm)	11.5" (29.2cm)	10.125" (25.7cm)
G12A	2 Hours 	◐	✓	✓	◐	Belt	Aluminum	1/2 HP	12" (30.48cm)	1/2" (1.27cm)	8.75" (22.2cm)	10" (25.4cm)	8.25" (21cm)
G12	2 Hours 	◐	✓		◐	Belt	Aluminum	1/2 HP	12" (30.48cm)	9/16" (1.43cm)	8.75" (22.2cm)	10" (25.4cm)	8.25" (21cm)
G10	1 Hour 	◐	✓		◐	Belt	Aluminum	1/3 HP	10" (25.40cm)	9/16" (1.43cm)	7.25" (18.4cm)	9.5" (24.13cm)	7.375" (18.7cm)
<b>Globe Chefmate and C-Series Economy Slicers</b>													
C12	1 Hour 	◐	✓		◐	Belt	Aluminum	1/3 HP	12" (30.48cm)	9/16" (1.43cm)	8" (20.32cm)	9.75" (24.77cm)	8.62" (21.89cm)
C10	30 Minutes 	◐	✓		○	Belt	Aluminum	1/4 HP	10" (25.40cm)	9/16" (1.43cm)	6.87" (17.45cm)	8.62" (21.89cm)	7.25" (18.42cm)
C9	< 30 Minutes 	◐	✓		○	Belt	Aluminum	1/4 HP	9" (22.86cm)	9/16" (1.43cm)	6.25" (15.88cm)	7.25" (18.42cm)	6.5" (16.51cm)



# Guía de la Selección de la Máquinas de Cortar

shop.dinecompany.com

Núm. de modelo	Volumen de rebanado //// (30 Minutos a todo el día)	Indice de precisión al rebanar	Manual (Rebanado a pedido)	Automático (Rebanado a granel)	El rebanar del queso	Tipo de Transmisión	Construcción	Motor	Lámina (Diámetro)	Gruaso máximo de la rebanda	Capacidad del Corte		
											D (Diámetro)	W (Anchura)	H (Altura)
<b>Globe P-Series Heavy Duty Premium Slicers</b>													
3600P - 4600P	Todo el día 	●	✓		●	Engranaje	Acero Inoxidable	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	7.5" (19.50cm)	11.6" (29.46cm)	9" (22.86cm)
3850P (2 Velocidades)	Todo el día 	●	✓	✓	●	Engranaje	Acero Inoxidable	1/2 HP	13" (33.02cm)	1-1/4" (3.18cm)	7.5" (19.50cm)	11.6" (29.46cm)	9" (22.86cm)
3975P - 4975P (9 Velocidades)	Todo el día 	●	✓	✓	●	Engranaje	Acero Inoxidable	1/2 HP	13" (33.02cm)	1-14" (3.18cm)	7.5" (19.50cm)	11.6" (29.46cm)	9" (22.86cm)
<b>Globe G-Series Medium Duty Slicers</b>													
GC512	4 Horas 	◐	✓		◐	Engranaje	Aluminio/ Acero Inoxidable	1/3 HP	12" (30.48cm)	7/8" (2.22cm)	7.5" (19.50cm)	10" (25.40cm)	8.75" (22.23cm)
G14	3 Horas 	◐	✓		◐	Correa	Aluminio	1/2 HP	14" (35.56cm)	9/16" (1.43cm)	9.75" (24.8cm)	11.5" (29.2cm)	10.125" (25.7cm)
G12A	2 Horas 	◐	✓	✓	◐	Correa	Aluminio	1/2 HP	12" (30.48cm)	1/2" (1.27cm)	8" (20.32cm)	9.5" (24.13cm)	8.5" (21.59cm)
G12	2 Horas 	◐	✓		◐	Correa	Aluminio	1/2 HP	12" (30.48cm)	9/16" (1.43cm)	8" (20.32cm)	9.5" (24.13cm)	8.5" (21.59cm)
G10	1 Horas 	◐	✓		◐	Correa	Aluminio	1/3 HP	10" (25.40cm)	9/16" (1.43cm)	8" (20.32cm)	9.5" (24.13cm)	8.5" (21.59cm)
<b>Globe Chefmate and C-Series Economy Slicers</b>													
C12	1 Horas 	◐	✓		◐	Correa	Aluminio	1/3 HP	12" (30.48cm)	9/16" (1.43cm)	8" (20.32cm)	9.75" (24.77cm)	8.62" (21.89cm)
C10	30 Minuto 	◐	✓		○	Correa	Aluminio	1/4 HP	10" (25.40cm)	9/16" (1.43cm)	6.87" (17.45cm)	8.62" (21.89cm)	7.25" (18.42cm)
C9	< 30 Minuto 	◐	✓		○	Correa	Aluminio	1/4 HP	9" (22.86cm)	9/16" (1.43cm)	6.25" (15.88cm)	7.25" (18.42cm)	6.5" (16.51cm)